



LED TECHNOLOGY

**9300 sqm**  
Illuminated area

**ENGINE POWERED Line**



Operation: **ENGINE POWERED**  
fuel tank capacity 220 litres  
Kubota Z482


## X-BOX 4x320W 48V LED - 8,5M



### FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- **Standard light sensor for machine power on and off**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- **Fully banded tank, 110%**
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization


**LOW**   
reduced  
transport costs

**RUNNING TIME**  
 220 litres tank  
**400 h**  
Low fuel consumption

**NOISE**   
level 65 dB(A) at 7m

**9300 sqm**  
illuminated area 

  
**VERY COMPACT** dimensions

**22 units**  
per truck 

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)		
		1200x1200x2560 (LxWxH)		2390x2390x8500 (LxWxH)		1030	
Floodlights	Type	Power (each)	Floodlights number	Options	Illuminated area (sqm)		
	Led	320W	4	Timer	9300		
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Options		
	Hydraulic	8,5 m	110 km/h	340°	Timer		
Alternator	Model	Frequency (Hz)	Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets	
	Synchronous	50	H	IP 23	3,5kVA - 230V	1 kVA	
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level dB(A) at 7m
	Kubota Z482*	Diesel	1500	220	0,55	400 h	65

\* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used