



Lighting Towers

LED TECHNOLOGY

480 sqm

Illuminated area



PIR MOTION
SENSOR


Solar Line



T-ZERO^{PRO}
X-POLE

X-POLE
SOLAR
2X30W LED - 5,5M

T-ZERO^{PRO}



Operation:
solar panel 200W
power battery pack 1024 Wh

X-POLE SOLAR 2x30W LED - 5,5M

T-ZERO PRO



FEATURES

- In house innovated controller that can regulate power output
- **Life P04 lithium-ion battery pack**
- High efficiency solar panel protected against all weather conditions
- High Luminous LED head complete with new light distribution lens design
- 5 sections manual vertical tower
- 5,5 m max height
- Galvanized metalworks
- 80 µm powder coating
- Forklift pockets for effective handling
- Strong galvanized base
- **PIR motion sensor as standard feature**

ZERO emissions	ZERO fuel costs	ZERO noise	MINIMAL sevice
MONOCRYSTALLINE SOLAR MODULE	480 sqm illuminated area	PIR MOTION SENSOR	anti TYPHOON
25 units per truck			

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
	1500x722x2366 (LxWxH)		1500x722x5500 (LxWxH)		403
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)
	Led	30W	2	65	480
Mast	Lifting method		Max Height	Max Wind Speed	
	Manual		5,5 m	80 km/h	
Batteries	Type	Batteries number	Power Battery pack	Expected battery cycle	
	LITHIUM	1	1024 Wh	2000	
Solar panel	Power (each)	Running time with solar mode	Min. working full bright	Min. working dim mode	
	200W		15 h	58 h	
Optional	4 Adjustable Height Stabilizers				