



METAL HALIDE

4200 sqm
Illuminated area



Construction
& work sites



Gas, oil & mining
operations



Special
events




Emergency



Military
applications

ENGINE POWERED Line



Operation: **ENGINE POWERED**
fuel tank capacity 80 litres
Kubota D1105

X-START
4X1000W - MH - 8M

X-START


4x1000W - MH - 8M



FEATURES



- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)		
	2560x1370x2560 (LxWxH)		2560x2570x8000 (LxWxH)		770		
Floodlights	Type	Power (each)	Floodlights number	Illuminated area (sqm)			
	Metal halide	1000W	4	4200			
Mast	Lifting method	Max Height	Max Wind Speed	Rotation			
	Manual	8 m	80 km/h	340°			
Alternator	Model	Frequency (Hz)	Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets	
	Synchronous	50	H	IP 23	8kVA - 230V	3 kVA	
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level dB(A) at 7m
	Kubota D1105*	Diesel	1500	80	1,60	50 h	65

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used